




CASCOO. Stainless Steel Castors.



Do you get upset to your castor application for rust, lower class & poor looking?  
Change to CASCOO - a cutting edge stainless steel castor. Which will give you  
not only excellent castor function but also cheerful face on your equipment.

**CASCOO. Stainless Steel Castors. CASCOO Innovation.  
Series NON0L0N**



Rim: Polyamide  
Tread: Polyamide  
Bearing: Plain bearing in stainless steel  
Threadguard: Without  
Load capacities: 130kg - 200kg  
Diameters: 80 mm - 125 mm  
Temperature Range: - 20° C - + 60° C



swivel castor	mm	mm	mm	mm	mm	mm	Kg
SIP26SC080NON0L0N	080	96X80	80/77x60	9	36	108	130
SIP26SC100NON0L0N	100	96X80	80/77x60	9	36	128	150
SIP36SC125NON0L0N	125	96X80	80/77x60	9	36	155	200




fixed castor	mm	mm	mm	mm	mm	Kg
FIP22SC080NON0L0N	080	96X80	80/77x60	9	108	130
FIP22SC100NON0L0N	100	96X80	80/77x60	9	128	150
FIP32SC125NON0L0N	125	96X80	80/77x60	9	155	200



swivel castor with total brake	mm	mm	mm	mm	mm	mm	mm	Kg
TIP26SC080NON0L0N	080	96X80	80/77x60	9	36	108	115	130
TIP26SC100NON0L0N	100	96X80	80/77x60	9	36	128	115	150
TIP36SC125NON0L0N	125	96X80	80/77x60	9	45	155	120	200

**CASCOO. Stainless Steel Castors. CASCOO Innovation.  
Series NON0L0N**



Rim: Polyamide  
Tread: Polyamide  
Bearing: Plain bearing in stainless steel  
Threadguard: Without  
Load capacities: 130kg - 200kg  
Diameters: 80 mm - 125 mm  
Temperature Range: - 20° C - + 60° C



swivel castor with bolt hole	mm	mm	mm	mm	Kg
HIH36SC080NON0L0N	080	13	36	106	130
HIH36SC100NON0L0N	100	13	36	126	150
HIH86SC125NON0L0N	125	13	40	153	200



swivel castor with bolt hole total brake	mm	mm	mm	mm	mm	Kg
BIH36SC080NON0L0N	080	13	36	106	115	130
BIH36SC100NON0L0N	100	13	36	126	115	150
BIH86SC125NON0L0N	125	13	45	153	120	200



wheel only	mm	mm	mm	mm	Ø	Kg
080NON0L0N	080	32	40	12	M8	130
100NON0L0N	100	32	40	12	M8	150
125NON0L0N	125	32	50	12	M8	200

**CASCOO. Stainless Steel Castors. CASCOO Innovation.  
Series N2U6Q0N**



Rim: Polyamide  
Tread: Thermoplastic Polyurethane 95° Shore A  
Bearing: Roller bearing in stainless steel  
Threadguard: Without  
Load capacities: 130kg - 200kg  
Diameters: 80 mm - 125 mm  
Temperature Range: - 20° C - + 60° C



swivel castor	mm	mm	mm	mm	mm	mm	Kg
SIP26SC080N2U6Q0N	080	96X80	80/77x60	9	36	108	130
SIP26SC100N2U6Q0N	100	96X80	80/77x60	9	36	128	150
SIP36SC125N2U6Q0N	125	96X80	80/77x60	9	36	155	200




fixed castor	mm	mm	mm	mm	mm	Kg
FIP22SC080N2U6Q0N	080	96X80	80/77x60	9	108	130
FIP22SC100N2U6Q0N	100	96X80	80/77x60	9	128	150
FIP32SC125N2U6Q0N	125	96X80	80/77x60	9	155	200



swivel castor with total brake	mm	mm	mm	mm	mm	mm	mm	Kg
TIP26SC080N2U6Q0N	080	96X80	80/77x60	9	36	108	115	130
TIP26SC100N2U6Q0N	100	96X80	80/77x60	9	36	128	115	150
TIP36SC125N2U6Q0N	125	96X80	80/77x60	9	36	155	120	200

**CASCOO. Stainless Steel Castors. CASCOO Innovation.  
Series N2U6Q0N**



Rim: Polyamide  
Tread: Thermoplastic Polyurethane 95° Shore A  
Bearing: Roller bearing in stainless steel  
Threadguard: Without  
Load capacities: 130kg - 200kg  
Diameters: 80 mm - 125 mm  
Temperature Range: - 20° C - + 60° C



swivel castor with bolt hole	mm	mm	mm	mm	Kg
HIH36SC080N2U6Q0N	080	13	36	106	130
HIH36SC100N2U6Q0N	100	13	36	126	150
HIH86SC125N2U6Q0N	125	13	40	153	200




swivel castor with bolt hole total brake	mm	mm	mm	mm	mm	Kg
BIH36SC080N2U6Q0N	080	13	40	106	115	130
BIH36SC100N2U6Q0N	100	13	40	126	115	150
BIH86SC125N2U6Q0N	125	13	45	153	120	200



wheel only	mm	mm	mm	mm	mm	mm	Kg
080N2U6Q0N	080	32	40	12	M8		130
100N2U6Q0N	100	32	40	12	M8		150
125N2U6Q0N	125	32	50	15	M8		200

**CASCOO. Stainless Steel Castors. CASCOO Innovation.**  
**Series R4E2Q0N / R4E2S34**



Rim: Polyamide  
 Tread: High Quality Grey Elastic 65° Shore A  
 Bearing: Roller bearing / Single ball bearing in stainless steel  
 Threadguard: Without / Small plastic threadguard  
 Load capacities: 160kg - 200kg  
 Diameters: 100 mm - 125 mm  
 Temperature Range: - 20° C - + 60° C



swivel castor							
	mm	mm	mm	mm	mm	mm	Kg
SIP26SC100R4E2Q0N SIP26SC100R4E2S34		96X80	80/77x60	9	36	128	160
SIP36SC125R4E2Q0N SIP36SC125R4E2S34		96X80	80/77x60	9	40	155	200




fixed castor					
	mm	mm	mm	mm	Kg
FIP22SC100R4E2Q0N FIP22SC100R4E2S34		96X80	80/77x60	9	128
FIP32SC125R4E2Q0N FIP32SC125R4E2S34		96X80	80/77x60	9	155



swivel castor with total brake							
	mm	mm	mm	mm	mm	mm	Kg
TIP26SC100R4E2Q0N TIP26SC100R4E2S34		96X80	80/77x60	9	36	128	160
TIP36SC125R4E2Q0N TIP36SC125R4E2S34		96X80	80/77x60	9	40	155	200

**CASCOO. Stainless Steel Castors. CASCOO Innovation.**  
**Series R4E2Q0N / R4E2S34**



Rim: Polyamide  
 Tread: High Quality Grey Elastic 65° Shore A  
 Bearing: Roller bearing / Single ball bearing in stainless steel  
 Threadguard: Without / Small plastic threadguard  
 Load capacities: 160kg - 200kg  
 Diameters: 100 mm - 125 mm  
 Temperature Range: - 20° C - + 60° C



swivel castor with bolt hole				
	mm	mm	mm	Kg
HIH36SC100R4E2Q0N HIH36SC100R4E2S34		13	36	126
HIH86SC125R4E2Q0N HIH86SC125R4E2S34		13	40	153



swivel castor with bolt hole total brake							
	mm	mm	mm	mm	mm	mm	Kg
BIH36SC100R4E2Q0N BIH36SC100R4E2S34		13	36	126	115	150	
BIH86SC125R4E2Q0N BIH86SC125R4E2S34		13	40	153	120	150	



wheel only						
	mm	mm	mm	mm	Ø	Kg
100R4E2Q0N 100R4E2S34		35	40	12	M8	160
125R4E2Q0N 125R4E2S34		38	50	15	M8	200