



CASCOO. Waste Bin Castors.




The disposal of waste requires heavy castor but not poor wheels. An easy moving wheel is important for large & heavy waste bin application.

**CASCOO. Waste Bin Castors.
Series P4S4**



Rim: Polypropylene
Tread: Solid Rubber 85° Shore A
Bearing: Nylon Plain Bearing
Threadguard: Without
Load capacities: 175kg - 200kg
Diameters: 160 mm - 200 mm
Temperature Range: -20° C - +60° C



| swivel castor | mm | mm | mm | mm | mm | mm | Kg |
|-------------------|-----|---------|-----------|----|----|-----|-----|
| SWP58WC160P4S4P0N | 160 | 135X110 | 105x84/76 | 11 | 52 | 195 | 175 |
| SWP58WC200P4S4P0N | 200 | 135X110 | 105x84/76 | 11 | 55 | 238 | 205 |



| swivel castor back brake with hook | mm | mm | mm | mm | mm | mm | Kg |
|---------------------------------------|-----|---------|-----------|----|----|-----|-----|
| CWP58WC200P4S4P0N | 200 | 135X110 | 105x84/76 | 11 | 55 | 238 | 205 |



| swivel castor back brake with screw | mm | mm | mm | mm | mm | mm | Kg |
|--|-----|---------|-----------|----|----|-----|-----|
| AWP58WC160P4S4P0N | 160 | 135X110 | 105x84/76 | 11 | 52 | 195 | 175 |
| AWP58WC200P4S4P0N | 200 | 135X110 | 105x84/76 | 11 | 55 | 238 | 205 |




| wheel only | mm | mm | mm | mm | Ø | Kg |
|------------|-----|----|----|----|-----|-----|
| 160P4S4P0N | 160 | 50 | 60 | 20 | M12 | 175 |
| 200P4S4P0N | 200 | 50 | 60 | 20 | M12 | 205 |

**CASCOO. Waste Bin Castors.
Series SBS4**



Rim: Steel Sheet
Tread: Solid Rubber 85° Shore A
Bearing: Roller Bearing
Threadguard: Without
Load capacities: 205kg
Diameters: 200 mm
Temperature Range: -20° C - +60° C



| swivel castor | mm | mm | mm | mm | mm | mm | Kg |
|-------------------|-----|---------|-----------|----|----|-----|-----|
| SWP58WC200SBS4R0N | 200 | 135X110 | 105x84/76 | 11 | 55 | 238 | 205 |



| swivel castor back brake with hook | mm | mm | mm | mm | mm | mm | Kg |
|---------------------------------------|-----|---------|-----------|----|----|-----|-----|
| CWP58WC200SBS4R0N | 200 | 135X110 | 105x84/76 | 11 | 55 | 238 | 205 |



| swivel castor back brake with screw | mm | mm | mm | mm | mm | mm | Kg |
|--|-----|---------|-----------|----|----|-----|-----|
| AWP58WC200SBS4R0N | 200 | 135X110 | 105x84/76 | 11 | 55 | 238 | 205 |



| wheel only | mm | mm | mm | mm | Ø | Kg |
|------------|-----|----|----|----|-----|-----|
| 200SBS4R0N | 200 | 50 | 60 | 20 | M12 | 205 |

**CASCOO. Waste Bin Castors.
Series P4S4**



Rim: Polypropylene
 Tread: Solid Rubber 85° Shore A
 Load capacities: 100kg
 Diameters: 200 mm
 Temperature Range: - 20° C - + 60° C



| wheel for waste bin |  mm |  mm |  mm |  mm |  mm |  Kg |
|---------------------|--|--|--|--|--|--|
| 200P4S4Z0N | 200 | 50 | | | ∅ | 100 |



| solid axle for waste bin |  mm |  mm |
|--------------------------|--|--|
| A460S0 | 460 | 21.5 |
| A552S0 | 552 | 21.5 |



| semi-hollow axle for waste bin |  mm |  mm |  mm |
|--------------------------------|--|--|--|
| A460SE20 | 460 | 21.5 | 2.0 |
| A552SE20 | 552 | 21.5 | 2.0 |



| hollow axle for waste bin |  mm |  mm |  mm |
|---------------------------|--|--|--|
| A460HO18 | 460 | 21.5 | 1.8 |
| A552HO18 | 552 | 21.5 | 1.8 |
| A460HO25 | 460 | 21.5 | 2.5 |
| A552HO25 | 552 | 21.5 | 2.5 |

